

GEGRÜNDET 1892

Rektol Klassik, Korbach



Fabrik und Grosshandlung
individueller Oele und Fette

REKTOL OIL CHANGE FLUID

Towards the end of an oil change interval or for "delayed" oil changes, the cleaning agents of the engine oil are used up. That there may be deposits in the engine, which would be solved only by the fresh engine oil. Our oil change fluid causes an intensive engine cleaning shortly before the oil change and improves, accelerates the drainage of used oil in the engine. A 300ml tin is placed in the warm engine shortly before an oil change (for oil fillings of 4 to 6 litres). After the engine has run idle for approx. 15 minutes, the used oil can be drained off. Attention: do not use for driving.

-
- Highest cleaning effect
 - 300ml package for 4 liters to 6 liters engine oil
 - Neutral to sealing material
-

SPECIFICATION

CONTAINS HIGH-DOSE DETERGENTS COMBINED WITH ANTIFOAM AND CORROSION PROTECTION.

Available in the following packaging sizes:

- 0,3 litre

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de