

GEGRÜNDET 1892

Rektol Klassik, Korbach



Fabrik und Grosshandlung
individueller Oele und Fette

REKTOL SF 15W-40

Premium turbo multigrade engine oil, formulated for use in many heavy duty petrol and diesel engines. Suitable for difficult operating conditions and highly turbocharged engines. This product contains increased levels ZDDP for improved wear protection.

- improved cold start behaviour
- rapidly build up oil pressure
- increased wear protection for the start and warm-up phase
- stable lubricating film
- reliable cleaning efficiency

Furthermore Rektol SF 15W-40 is suitable for engines of the older construction machines as well as for circular lubrication and hydrostatic drives. The original oil formulation according to specification API SF/CD was an inherent part of our product range in our in-house production from 1980s until the 1990s.

SPECIFICATIONS

SAE 15W-40	HISTORICAL TERMS:
API-SF/CD	MIL-L-2104-C/D/E, MIL-L-46152-C, MIL-L-45199-B, FORD M2C-153-B/D FORD SSM-2C-9011-A, GM 6048-M / 6049-M, CATERPILLAR SERIES 3, CCMC G-2/D-2/D-3, MB 227.1

TYPICAL CHARACTERISTICS

Density at 15°C	g/ml	DIN 51757	0,88
Flash point	°C	DIN ISO 2592	>220
Pour point	°C	DIN ISO 3016	- 22
Viscosity at 40°C	mm ² /sec	DIN 51562	109
Viscosity at 100°C	mm ² /sec	DIN 51562	15

Available in the following packaging sizes:

- 2 litre tin can
- 5 litre can
- 20 litre can

Special packaging sizes are available on request.

Issue: February 2018



Einsatz nach Vorschriften der Motorenhersteller.

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen.

Rektol GmbH & Co. KG · Am Kniep 2 · 34497 Korbach · Tel.: 0 56 31-95 30-0 · Fax: 0 56 31-95 30-25 · E-Mail: info@rektol.de · Internet: www.rektol.de